



# 2 TRACKS TENSIONERS



	10 t	15 t	20 t	35 t	55 t	70 t
--	------	------	------	------	------	------

BRAKING	t	13	25	27	47	75	90
PULLING POWER SUPPLY		ELEC.	HYDRAU.	HYDRAU.	HYDRAU.	ELEC.	HYDRAU.
LAYING SPEED HALF LOAD	m/min	40	40	20	40	40	28
LAYING SPEED FULL LOAD	m/min	40	16	20	40	40	25
MAX. RECOVERY SPEED	m/min	10	10	20	10	20	25
PRODUCT TYPE*	F / R / U / W	F / R	F / R / U	F / R / U	F / R / U	F / R	F / R
PRODUCT DIAMETER RANGE	mm	40 > 115	50 > 630	100 > 400	50 > 600	50 > 600	100 > 500
MAX. CLEARANCE	mm	250	450	500	700	760	600
CLAMPING FORCE RANGE	t/m	40	40	60	10 > 60	10 > 62	10 > 62
CONTACT LENGHT	m	1400	3000	2400	2400	2400	3700
MIN. FRICTION FACTOR		0,09	0,07	0,07	0,07	0,25	0,18
OVERALL DIMENSIONS							
LENGHT	mm	3 400	6 200	5 700	5 800	5 800	6 000
WIDE	mm	1 400	3 600	4 500	4 600	4 600	4 600
HEIGHT	mm	2 500	3 200	3 600	4 000	5 200	5 050
WEIGHT	t	9	15	16	28	39	43

\*FLEXIBLE / RIGID / UMBILICAL / WIRE ROPE

Non contractual data | Contact us for details | REEL © 2016