



SPLITTED A&R WINCHES



Highlights

- › DNV Certified
- › Pulling traction up to 800 Te on demand
- › Electrical or hydraulic
- › Synchronized dual pulling system
- › Single wire rope 630 Te Active Heave Comp. to lay up to 3,2 m waves

	200 t		300 t		350 t		450 t		650 t							
TRACTION WINCH	t	200		310		360		450		630						
STORAGE WINCH	t	18		18		25		25		32						
BRAKING CAPACITY	t		270		27	350		495		40	700					
MAX SPEED NO LOAD	m/min	/	40	/	13,5	/	13,5	/	30	/	30					
MAX SPEED HALF LOAD	m/min	/	40 @ 100	/	13,5 @ 200	/	13,5 @ 175	/	30 @ 225	/	30 @ 350					
MAX SPEED FULL LOAD	m/min	/	20	/	12	/	10	/	16	/	17					
WIRE ROPE DIAMETER	mm		76		96		109		121		136					
MBL	t		510		790		1 000		1 200		1 530					
STORAGE CAPACITY	m		3 000		4 000		4 000		3 500		4 000					
MOTOR POWER INSTALLED																
STORAGE*	kW		2x100		2x44		2x105		2X105		2X130					
TRACTION	kW		4x220		6x130		8x192		8X240		10X240					
OVERALL DIMENSIONS																
LENGHT	mm		6 200	6 100		6 900	6 800		0	0		8 700	7 400		9 600	7 400
WIDE	mm		5 400	4 600		6 400	5 900		0	0		7 800	7 100		7 300	5 700
HEIGHT	mm		3 500	2 600		6 300	4 200		0	0		6 600	6 300		7 700	3 700
WEIGHT	t		123	57		240	74		296	99		70	106		94	150
DIRECT SPOOLING			Y	N		Y	N		Y	N		Y	N		Y	N
AUTOMATIC SPOOLING			N	Y		N	Y		N	Y		N	Y		N	Y
CONSTANT TENSION			Y	Y		Y	Y		Y	Y		Y	Y		Y	Y

* Spooling motor not included

Non contractual data | Contact us for details | REEL © 2016